

XYZ PROTURNS RLX 425

Available as a 1.25 and 2 Metre Gap Bed Lathe
 Swing Over Bed: 480mm
 Distance Between Centres: 1,250 / 2,000mm
 Spindle Bore 80mm
 Spindle: 2,500 rpm



XYZ PROTURNS RLX 425 x 1.25 metre

Specification	XYZ RLX 425 1.25 and 2 metre
Swing Over Bed	480mm
Swing in Gap	700mm
Gap in front of Faceplate	170mm
Swing over Cross Slide	257mm
Cross Slide Travel	230mm
Distance between Centres	1,250 / 2,000mm
Maximum Cutting Length	1,080 / 1,900mm
Spindle Bore	80mm
Spindle Nose	D1-8 Camlock
Spindle Taper	MT5 in bush
Spindle	7.5kW (10 hp)
Spindle Speeds	25 - 2,500 rpm
Speed Ranges	3 Ranges (25 - 300, 50 - 850 & 140 - 2,500 rpm)
Tailstock Travel	160mm
Tailstock Taper	MT5
Tailstock Diameter	75mm
Bed Width	370mm
Machine Weight	2,700 / 3,700kg
Footprint	2,600 x 1,480 x 1,830mm/3,450 x 1,600 x 1,910mm

Standard Equipment

- 250mm 3 Jaw Chuck.
- Constant Surface Speed.
- TRAKing®.
- 3 Range Headstock.
- Quick Change Toolpost with 6 Holders.
- Rapid Traverse with Joy Stick.
- Air Assist Tailstock.
- Interlocked Chuck Guard and Main Guard.
- Auto Lubrication.
- Flood Coolant.
- Worklight.
- Centres and Bushes.

Optional Equipment

- Advanced Features.
- Verify Solid Model Graphics.
- DXF File Converter.
- Offline Programming.
- Drilling Attachment.
- Adjustable Backstop.
- Faceplates, Steadies, Chucks and Collet Chucks.
- 4 or 8 Station Auto Indexing Toolpost.
- Swarf Conveyor.



Part of the XYZ Catalogue 2024/25 which includes:
 ProtoTRAK® Lathes.
 Turning Centres.
 XL Extra Large Lathes.
 Oil Country Lathes.
 Manual Mills & Lathes.
 Grinders.
 Tooling & Accessories.



Visit www.xyzmachinetools.com or our YouTube channel to see the video.