XYZ PROTURN RLX 555

Available as I and I.75 Metre Gap Bed Lathe

Swing Over Bed: 560mm

Distance Between Centres: 1,000 / 1,750mm

Spindle Bore: 104mm Spindle: 1,800 rpm



Specification	XYZ RLX 555
	I and I.75 metre
Swing Over Bed	560mm
Swing in Gap	780mm
Gap in front of Faceplate	227mm
Swing over Cross Slide	350mm
Cross Slide Travel	280mm
Distance between Centres	I,000 / I,750mm
Maximum Cutting Length	900 / I,650mm
Spindle Bore	I04mm
Spindle Nose	DI-11 Camlock
Spindle Taper	MT5 in bush
Spindle	11.2kW (15hp)
Spindle Speeds	30 - 1,800rpm
Speed Ranges	2 Ranges (30 - 375 & 140 - 1,800,rpm)
Tailstock Travel	I 60mm
Tailstock Taper	MT5
Tailstock Diameter	90mm
Bed Width	370mm
Machine Weight	3,200kg / 4,100kg
Footprint	2,600 × 1,600 × 1,930mm/3,510 × 1,550 × 1,930mm



Part of the XYZ Catalogue 2024/25 which includes: ProtoTRAK® Lathes. Turning Centres. XL Extra Large Lathes. Oil Country Lathes. Manual Mills & Lathes. Grinders. Tooling & Accessories.

Standard Equipment

- 315mm 3 Jaw Chuck.
- **■** Constant Surface Speed.
- TRAKing®.
- 2 Range Headstock.
- Quick Change Toolpost with 6 Holders.
- Rapid Traverse with Joy Stick.
- Air Assist Tailstock.
- Interlocked Chuck Guard and Main Guard.
- Auto Lubrication.
- Flood Coolant.
- Worklight.
- **■** Centres and Bushes.

Optional Equipment

- Advanced Features.
- Verify Solid Model Graphics.
- **DXF** File Converter.
- Offline Programming.
- Drilling Attachment.
- Adjustable Backstop.
- Faceplates, Steadies, Chucks.
- 4 or 8 Station Auto Indexing Toolpost.
- Swarf Conveyor.



Visit www.xyzmachinetools.com or our YouTube channel to see the video.