XYZ PROTURN RLX 780

Available as 1.5 and 3 Metre Gap Bed Lathe

Swing Over Bed: 780mm

Distance Between Centres: 3,000mm

Spindle Bore: 160mm Spindle: 1,300 rpm



| Specification | XYZ RLX 780 1.5 and 3 metre |
|---------------------------|--|
| Swing Over Bed | 780mm |
| Swing in Gap | I,090mm |
| Gap in front of Faceplate | 157mm |
| Swing over Cross Slide | 535mm |
| Cross Slide Travel | 430mm |
| Distance between Centres | 1,500 / 3,000mm |
| Maximum Cutting Length | I,400 / 2,900mm |
| Spindle Bore | I 60mm |
| Spindle Nose | A2-11 |
| Spindle Taper | MT6 in bush |
| Spindle | 32kW (43hp) |
| Spindle Speeds | 20 - 1,300 rpm |
| Speed Ranges | 2 Ranges (20 - 415 & 40 - 1,300 rpm) |
| Tailstock Travel | 200mm |
| Tailstock Taper | MT6 |
| Tailstock Diameter | 105mm |
| Bed Width | 500mm |
| Machine Weight | 6,400kg / 8,600kg |
| Footprint | $3,904 \times 2,170 \times 2,180$ mm/ $5,455 \times 2,170 \times 2,180$ mm |



Part of the XYZ Catalogue 2024/25 which includes: ProtoTRAK® Lathes. Turning Centres. XL Extra Large Lathes. Oil Country Lathes. Manual Mills & Lathes. Grinders. Tooling & Accessories.

Standard Equipment

- 500mm 3 Jaw Chuck.
- **■** Constant Surface Speed.
- TRAKing®.
- 2 Range Headstock.
- Quick Change Toolpost with 6 Holders.
- Rapid Traverse with Joy Stick.
- Air Assist Tailstock.
- Interlocked Chuck Guard and Main Guard.
- Auto Lubrication.
- Flood Coolant.
- Worklight.
- Centres and Bushes.

Optional Equipment

- Advanced Features.
- Verify Solid Model Graphics.
- **DXF** File Converter.
- Offline Programming.
- Drilling Attachment.
- Faceplates, Steadies and Chucks.
- 8 Station Auto Indexing Toolpost.
- Swarf Conveyor.
- Rear Mounted Chuck.



Visit www.xyzmachinetools.com or our YouTube channel to see the video.