

3 HP VARIABLE SPEED HEAD 42" x 9" (1,069 x 228mm) TABLE 24" x 12" (610 x 305mm) TRAVEL

This is the best starting place for those keen to take advantage of CNC milling with the minimum of outlay.

The **XYZ KMX 1500** is the entry level machine and control, after only one day you will wonder why you ever used a manual mill.

Standard Equipment

Vari Speed 2 Range Head.

Chrome Slides.

3 Axis DRO.

2 Axis CNC.

Verify Solid Model Graphics.

Precision Ground Ballscrews.

Coolant.

Work Light.

Auto Lubrication.

Steel Swarf Tray.

Interlocked Guarding.

Optional Equipment

TRAKing®.

Riser Blocks.

Air Power Drawbar.


4th Axis DRO.

Offline Software.

Tooling, Vices etc.

Parasolid and DXF Convertors.

Millstar (Quill DRO).



Part of the XYZ Milling Catalogue which includes:
ProtoTRAK® Turret Mills.
ProtoTRAK® Bed Mills.
Vertical Machining Centres.
4+1 & 5 Axis Simultaneous VMCs.
Mobile Robotic Automation.
Manual Mills & Lathes.

Tooling & Accessories.

Grinders.



	XYZ KMX 1500
Spindle drive motor	2.25 kW (3 HP)
Vari speed range high / low	60-4,200 rpm
Table size	1,069 × 228 mm
T slots-3	15.9 mm 3 off
Longitudinal travel - X axis	610 mm
Cross travel - Y axis	305 mm
Knee vertical travel - Z axis	362 mm
Slide type	Hardened Ground
Ram travel	390 mm
Spindle taper	R8 / 30 ISO optional
Quill power feeds	.038 .076 .15 mm
Quill travel	127 mm
Quill diameter	86 mm
Max table load	350 kg
Swivel on turret	360°
Head tilt front to back	45°-45°
Head tilt left to right	90°-90°
Max throat depth	686 mm
Net weight approx	1,250 kg



Visit www.xyzmachinetools.com or the YouTube channel to see the video.