

XYZ PROTURN RLX 1630

SWING OVER BED 400mm
SPINDLE BORE 54mm
DISTANCE BETWEEN CENTRES 760mm
MAX 2,500 RPM



	XYZ RLX 1630
Swing over bed mm	400 mm
Swing in gap	<i>not applicable</i>
Gap in front of faceplate	<i>not applicable</i>
Swing over cross slide	218 mm
Cross slide travel	216 mm
Distance between centres	760 mm
Maximum cutting length	760 mm
Spindle bore	54 mm
Spindle nose	D1-6 camlock
Spindle taper	MT4 in bush
Spindle motor	5.75 kW (7.5 HP)
Spindle speeds	150-2,500 rpm
Tailstock travel	127 mm
Tailstock taper	MT4
Tailstock diameter	60 mm
Bed width	320 mm
Footprint L x D x H	2,090 x 1,200 x 1,800 mm
Weight	1,550 kg

Standard Equipment

200mm 3 Jaw Chuck.
Constant Surface Speed.
TRAKing®.
Single Range Headstock.
Quick Change Toolpost with 6 Holders.
Rapid Traverse with Joy Stick.
Tailstock.
Interlocked Chuck Guard and Main Guard.
Auto Lubrication.
Flood Coolant.
Worklight.
Centres and Buses.

Optional Equipment

Advanced Features.
Verify Solid Model Graphics.
DXF File Converter.
Offline Programming.
Adjustable Back Stop.
Faceplates, Steadies, Chucks and Collet Chucks.
4 Station Auto Indexing Toolpost.
Swarf Conveyor.



Part of the **XYZ Turning Catalogue** which includes:
ProtoTRAK® Lathes.
Turning Centres.
XL Extra Large Lathes.
Oil Country Lathes.
Mobile Robotic Automation.
Manual Mills & Lathes.
Grinders.
Tooling & Accessories.



Visit www.xyzmachinetools.com or
the YouTube channel to see the video.