


# XYZ PROTURN RLX 555

**I and 1.75 METRE GAP BED LATHE**  
**SWING OVER BED 560mm**  
**SPINDLE BORE 104mm**  
**DISTANCE BETWEEN CENTRES 1,000 or 1,750mm**  
**MAX 1,800 RPM**



	<b>XYZ RLX 555- I and 1.75 metre</b>
Swing over bed	560 mm
Swing in gap	780 mm
Gap in front of faceplate	227 mm max
Swing over cross slide	350 mm
Cross slide travel	280 mm
Distance between centres	1,000 / 1,750 mm
Maximum cutting length	900 / 1650 mm
Spindle bore	104 mm
Spindle nose	D 1-11 camlock
Spindle taper	MT7 in bush
Spindle motor	11 kW (15HP)
Spindle speeds	30-1,800 rpm (2 ranges)
Tailstock travel	160 mm
Tailstock taper	MT 5
Tailstock diameter	90 mm
Bed width	370 mm
Footprint L x D x H	2,600 / 3,450 x 1,600 x 1,910 mm
Weight	3,000 / 4,100 kg

## Standard Equipment

**315mm 3 Jaw Chuck.**  
**Constant Surface Speed.**  
**TRAKing®.**  
**2 Range Headstock.**  
**Quick Change Toolpost with 6 Holders.**  
**Rapid Traverse with Joy Stick.**  
**Air Assist Tailstock.**  
**Interlocked Chuck Guard and Main Guard.**  
**Auto Lubrication.**  
**Flood Coolant.**  
**Worklight.**  
**Centres and Bushes.**

## Optional Equipment

**Advanced Features.**  
**Verify Solid Model Graphics.**  
**DXF File Converter.**  
**Offline Programming.**  
**Drilling Attachment.**  
**Adjustable Back Stop.**  
**Faceplates, Steadies, Chucks and Collet Chucks.**  
**4 or 8 Station Auto Indexing Toolpost.**  
**Swarf Conveyor.**



**Part of the XYZ Turning Catalogue which includes:**  
**ProtoTRAK® Lathes.**  
**Turning Centres.**  
**XL Extra Large Lathes.**  
**Oil Country Lathes.**  
**Mobile Robotic Automation.**  
**Manual Mills & Lathes.**  
**Grinders.**  
**Tooling & Accessories.**



Visit [www.xyzmachinetools.com](http://www.xyzmachinetools.com) or the YouTube channel to see the video.