

XYZ PROTURN RLX 555

Available as 1 and 1.75 Metre Gap Bed Lathe
 Swing Over Bed: 560mm
 Distance Between Centres: 1,000 / 1,750mm
 Spindle Bore: 104mm
 Spindle: 1,800 rpm



Specification	XYZ RLX 555 1 and 1.75 metre
Swing Over Bed	560mm
Swing in Gap	780mm
Gap in front of Faceplate	227mm
Swing over Cross Slide	350mm
Cross Slide Travel	280mm
Distance between Centres	1,000 / 1,750mm
Maximum Cutting Length	900 / 1,650mm
Spindle Bore	104mm
Spindle Nose	D1-11 Camlock
Spindle Taper	MT7 in bush
Spindle	11.2kW (15hp)
Spindle Speeds	30 - 1,800rpm
Speed Ranges	2 Ranges (30 - 375 & 140 - 1,800,rpm)
Tailstock Travel	160mm
Tailstock Taper	MT5
Tailstock Diameter	90mm
Bed Width	370mm
Machine Weight	3,200kg / 4,100kg
Footprint	2,600 x 1,600 x 1,930mm/3,510 x 1,550 x 1,930mm

Standard Equipment

- 315mm 3 Jaw Chuck.
- Constant Surface Speed.
- TRAKing®.
- 2 Range Headstock.
- Quick Change Toolpost with 6 Holders.
- Rapid Traverse with Joy Stick.
- Air Assist Tailstock.
- Interlocked Chuck Guard and Main Guard.
- Auto Lubrication.
- Flood Coolant.
- Worklight.
- Centres and Buses.

Optional Equipment

- Advanced Features.
- Verify Solid Model Graphics.
- DXF File Converter.
- Offline Programming.
- Drilling Attachment.
- Adjustable Backstop.
- Faceplates, Steadies, Chucks.
- 4 or 8 Station Auto Indexing Toolpost.
- Swarf Conveyor.



Part of the **XYZ Catalogue 2024/25** which includes:
 ProtoTRAK® Lathes.
 Turning Centres.
 XL Extra Large Lathes.
 Oil Country Lathes.
 Manual Mills & Lathes.
 Grinders.
 Tooling & Accessories.



Visit www.xyzmachinetools.com or our YouTube channel to see the video.