

XYZ KMX 2500

ProtoTRAK®

Spindle: 2.25 kW (3hp)

Variable Speed Head

Table Size: 1,245 x 228mm

Travels: 770 x 388mm

Guards removed for clarity



Great value, providing the perfect entry into 3 axis CNC Control on a Bed Mill

Standard Equipment and Features.

ProtoTRAK® KMX Control.

2 & 3 Axis CNC Control

4 Axis DRO (Quill & Head Interlinked).

Precision Ground Ballscrews.

Hi/Lo Gear Ranges.

Swarf Tray.

Auto Lubrication.

LED Worklight.

Coolant Pump.

UKCA/CE Approved Interlocked Guarding.

Optional Equipment.

Air Power Drawbar.

Electronic Handwheels.

ISO30 Spindle.

Spindle	2.25kW (3hp)
Spindle Speeds	60 - 3,500rpm
2 Speed Ranges	2 Ranges (60 - 420 & 500 - 3,500rpm)
Table Size	1,245 x 228mm (49" x 9")
T Slot Size	16mm (5/8")
T Slots	3 off
X Axis Table Travel	770mm (30.3")
Y Axis Table Travel	388mm (15.3")
Head Vertical Travel	530mm (20.9")
Spindle Taper	R8 (ISO30 Optional)
Quill Power Feeds	.038 .076 .15mm
Quill Travel	125mm (4.9")
Quill Diameter	85.7mm (3.37")
Max Table Load	600kg
Head Tilt Left to Right	+45° / -45°
Max Throat Depth	440mm (17.3")
Machine Weight	1,720kg