



HARDENED BOX SLIDEWAYS


Spindle: 32kW (43hp) 3,300 rpm Spindle Bore: 91mm Travels: 270 x 100mm x 600mm Machine Weight: 6,950kg




# The largest XYZ Y axis turning centre.

The **XYZ TC 320 LTY** is the largest Y axis turning centre in the XYZ range and provides users with exceptional capacity from a solid cast machine base. The addition

of the 100 mm Y axis (+/-50 mm) adds a degree of versatility to the machine that allows many parts to be machined complete, increasing productivity significantly.



The 'Y' axis of the XYZ TC 320 LTY can travel 50mm above and below centreline (100mm total travel), making easy work of most components that would normally require milling and turning operations.





### **Standard Equipment**

- Siemens 828D ShopTurn Touchscreen Control.
- PLC written by Siemens UK.
- Hydraulic 315mm 3 Jaw Chuck.
- Sauter 'German' VDI Turret.
- Renishaw Automatic Tool Setting Arm.
- Swarf Conveyor & Bin.
- VDI Turret.
- Full 'C' Axis.
- Live Tooling.
- I00mm Y axis.
- Programmable Hydraulic Tailstock.
- Through Tool and Flood Coolant.
- Remote Electronic Handwheel.
- USB Port.
- Networking.

#### **Optional Equipment**

- Parts Catcher.
- Collet Chuck.
- Bar Puller.
- LNS or Hydrafeed Bar Feed Systems.
- **Offline Programming.**
- Siemens CAD Reader.
- Contour Handwheel.
- Gear Hobbing.
- Polygon Turning.
- Advanced Swarf Management System.
- Hydraulic 380mm 3 Jaw Chuck\*.

Specification	XYZ TC 320 LTY
Power Chuck Diameter	300mm
Maximum Swing	450mm
Swing Over Carriage Cover	450mm
Maximum Turned Diameter	320mm
Maximum Turned Length	550mm
X Axis Travel	270mm
Y Axis Travel	100mm (+/- 50mm)
Z Axis Travel	600mm
Spindle Centre Height from Floor	1,230mm
Height from floor to spindle centre	1,040mm
Spindle Nose	A2-8
Spindle Bore (Drawtube Capacity)	91mm (78mm)
Spindle Front Bearing Internal Dia	130mm
Spindle Speeds	3,300 rpm
Spindle Motor	32kW (43hp)
Min Speed for Full Power	1,500 rpm
Rapid Feedrate	20 M/min
Slideway Type	Hardened Box Way
Ballscrew	X = 40mm / Y = 36mm / Z = 45mm
Servo Motor	X = II Nm / Y = II Nm / Z = I6 Nm
Toolchanger	12 Station 40 VDI Turret
Tool Section Size	25 x 25mm
Max Boring Bar Diameter	40mm
Tailstock Quill Taper	MT5
Quill Diameter	95mm
Quill Travel	125mm
Max Quill Thrust	2,300kg
Coolant Tank Capacity	200L
Coolant Pump Delivery	16 L/min @ 2.5 Bar
Machine Weight	6,950kg
Footprint	4,120 × 2,480 × 2,300mm

#### \* Renishaw Toolsetting arm has to be removed.

Conforming to ISO 13041	
Positional accuracy	+/- 5 microns
Repeatability	+/- 2 microns
Cutting accuracy over 100mm	10 microns
Geometric accuracy over 100mm	10 microns


## With Hard Box Way slides

The **XYZ TC 320 LTY** features the latest in high quality Hard Box Way slide technology.





Visit www.xyzmachinetools.com or our YouTube channel to see the video.



Part of the XYZ Catalogue 2024/25 which includes: ProtoTRAK<sup>®</sup> Lathes. Turning Centres. XL Extra Large Lathes. Oil Country Lathes. Manual Mills & Lathes. Grinders. Tooling & Accessories.